



GLOVER TYPE '202' REFUSE VEHICLE WITH BIN LIFT



Featuring

British design and manufacture.
Designed for simplicity of maintenance and operation.
Robust all-welded steel construction.
Designed for most popular makes of chassis.

Smooth quiet operation with hydraulic motor drive in place of complicated ram operated systems.
Large capacity hopper with low loading height.
Fast loading continuous or intermittent operation.



Bin lift equipment stowed



Bin lift equipment ready for use



1¼ cubic yard bin about to be loaded.

Specification

Body and Hopper Construction

All-welded zinc-coated steel with Cor-ten floor sweep plate and other wearing areas.

Packer Mechanism

Heavy duty packer plate carried on crank assemblies with pivoting top links and driven through roller chains by hydraulic motor and epicyclic reduction gear box. Hopper fitted with robust top hinges and lifted by single acting rams with safety check valves. Manual type locks secure hopper to body during loading.

Hydraulic System

Large capacity hydraulic tank at front of body with suction filter and engine driven gear type hydraulic pump protected by a full-flow relief valve incorporating a dump valve to pass oil back to tank when hydraulic services are not required. Separate control valves for operating hydraulic motor packer drive, discharge barrier and hopper lift.

Controls

Push-buttons on loading hopper for start, stop and reverse operation of packer mechanism and selector switch for continuous or intermittent operation. Controls in cab include hand throttle, control for engaging pump operation and remote controls for hopper lift and discharge barrier.

Bin Lifter

Bin lifting equipment can be fitted to both the 18 and 21 cu. yd. models of the Glover "202". The vehicle can be used as a manual loading vehicle with the bin lifting equipment stowed at high level at the rear of the body. This stowage is achieved at the roadside by simple hydraulic control. The hydraulic power required for this equipment is obtained from a secondary power take-off pump to avoid reducing packer plate pressure.

Safety Features

Full-width emergency stop bar on loading hopper. Rubber curtains in hopper and across lower edge of packer plate.

GENERAL DATA

Body Capacity	: 13.76cu. m. (18 cu. yds.)
Overall Height	: 3.32m. (10' 10¼") — 3.54m. (11' 7½") with cradle stowed
Overall Width	: 2.44m. (8' 0")
Hopper Capacity	: Approx. 1.15 cu.m. (1.5 cu. yds.)
Hopper Width (inside)	: 1.85m. (73")
Loading Height (unladen)	: 1.19m. (47")
Compaction ratio	: 4.5 to 1 for average loads
Packer rate	: Up to 4 cycles/min. (continuous)

Glover Webb & Liversidge Limited Municipal Vehicles



Sales & Service
Home & Overseas

GLOVER—HAMBLE

Hamble Lane, Hamble, Hampshire, SO3 5NY.
Telephone: 042-122-2811 Telex: 477527