UPSCALE RECYCLING EQUIPMENT



TOP SELECT SERIES

 A Labrie design innovation — the hydraulic "over top" loading recycler.

 A significant number of households throughout Canada and the United States are serviced by our trucks.

 The TOP SELECT SERIES has become the industry standard for pilot



projects and implementation of complete recycling programs.

 Labrie is designing and manufacturing the most advanced equipment for the end user, demonstrating our continuing commitment to the recycling industry.

UPSCALE RECYCLING EQUIPMENT

302, rue du Fleuve, Beaumont (Québec), Canada GOR 1CO, Tel.: (418) 837-3606 Fax: (418) 837-7698

THE ANSWER LINE: 1-800-463-6638



TOP SELECT 1000

"Single side loading"



TOP SELECT 2000

"Dual sides loading"

FEATURES

- Hydraulic over top loading device capable of dumping permanent recessed buckets.
- A unique feature: roof actuated by only two hydraulic cylinders to raise and lower the buckets.
- Engineered for safety, ease of operation and minimum maintenance.
- Can be fully loaded with 2 to 6 different recyclable materials weighing 5 to 6 tons.
- One to five movable swing-type compartment partitions adjustable to 12"
 centers, complete with interior doors.
- Overhead track for partition support while moving.
- Designed to minimize operator fatigue.
- Can average over 125 collection stops per hour under normal conditions.
- Exterior track, nylon guide, rollers and hooks: a unique system to guide and support the loading bucket and to ease dumping.

STANDARD SPECIFICATIONS



LENGTH: 20 ft. 8 in. / 6300 mm Interior Dimension

• HEIGHT: 72 in. / 1830 mm Interior Dimension

EXTERIOR WIDTH: 102 in. / 2591 mm

INTERIOR BODY WIDTH:

TOP SELECT 1000: 74 in. / 1880 mm at the bottom

89 in. / 2260 mm at the top

TOP SELECT 2000: 59 in. / 1500 mm at the bottom

89 in. / 2260 mm at the top

CAPACITY :

TOP SELECT 1000:31 cu. yd./23,7 m³
TOP SELECT 2000:29 cu. yd./22,1 m³

LOADING HEIGHT: 46 in. / 1168 mm

AVAILABLE OPTIONS

- Container attachment for 90 gallon roll carts.
- Plastic crusher.
- Air operated unlocking system on partition.

Due to our commitment to constant product improvement, all designs, specifications and components are subject to change at the manufacturer's sole discretion at any time without notice.

CHASSIS INSTALLATION (AVAILABLE OPTIONS)

- Installation on the chassis of your choice.
- Flat back cowl chassis with installation of a walk through insulated cab with sliding doors complete with a right hand side stand up drive with a step height of 18 inches.
- Modification and extension of a conventional cab on the right hand side for stand up drive with step height of 18 inches.