

TIPS THE SCALES IN YOUR FAVOR

The LEGAL ONE™ Front Loaders have all the speed and power of Maxon packers, but with a difference that allows you to haul higher legal payloads. That difference is the 12-sided body. This Maxon exclusive design gives you the 38 yard capacity you need with the lowest possible body weight.

The LEGAL ONE™ EAST packers have 8,000 lb. lift arms and weigh just 15,000 lbs. The LEGAL ONE™ WEST packers have 6,000 or 8,000 lb. arms and weigh just 13,900 lbs. Both models have the same 100,000 lb. packing force, the same 30 second packing cycle and the amazingly quick Maxon lift arm cycles of 16 seconds for the WEST

model and just 19 seconds for the EAST model.

LEGAL ONE™ bodies are made of super strong 100,000 PSI rated steel. Lower center of gravity and better weight distribution mean more stability, better fuel economy and less tire wear.

The 12-sided body even provides better rearview visibility for the driver.

When it comes to high productivity and low maintenance reliability, no other Front Loading packer can compete with the LEGAL ONE™ Front Loaders.

LEGAL ONE™
FRONT LOADERS
MAXON®

MODELS: LOE (EAST) • LOW (WEST)



LEGAL ONE™ EAST & WEST

LEGAL ONE™
FRONT LOADERS

PERFORMANCE SPECIFICATIONS

**MODEL
LOE (EAST)**

**MODEL
LOW (WEST)**

		MODEL LOE (EAST)	MODEL LOW (WEST)
	LIFT ARM CYCLE PACKER CYCLE ARM CAPACITY COMPACTION FORCE DUMP ANGLE	19 SECONDS 25-28 SECONDS 8,000 LBS. 100,000 LBS. 33°	16 SECONDS 25-28 SECONDS 6,000 LBS. or 8,000 LBS. 100,000 LBS. 33°
BODY & HOPPER	GROSS WEIGHT (Approx.) HOPPER CAPACITY (Usable) BODY CAPACITY* REAR (Bubble) DOOR OVERALL LENGTH (Including Canopy) OVERALL WIDTH OVERALL HEIGHT (Arms down)	15,000 LBS. 10 CUBIC YARDS 26 CUBIC YARDS 2 CUBIC YARDS 356" 98" 103"	13,900 LBS. 10 CUBIC YARDS 26 CUBIC YARDS 2 CUBIC YARDS 356" 98" 103"
*OTHER BODY SIZES AVAILABLE FOR SPECIAL APPLICATIONS.			
MATERIALS	BODY FLOOR FRONT BODY FLOOR REAR HOPPER SIDES (Lower) HOPPER SIDES (Upper) BODY SIDES BODY ROOF REAR DOOR PACKER BLADE LOWER FACE PACKER BLADE UPPER FACE PACKER TRACKS BODY, HOPPER & FLOOR BRACING	1/4" 10 GA. 7 GA. 10 GA. 12 GA. 12 GA. 12 GA. 1/4" 7 GA.	3/16" 12 GA. 7 GA. 12 GA. 13 GA. 13 GA. 12 GA. 1/4" 7 GA.
TOP, BOTTOM AND SIDES, LINED SQUARE OR RECTANGULAR STEEL TUBE All Material Special High Tensile Steel Min. Yield 100,000 PSI			
CYLINDERS	PACKER ARMS FORKS TAIL GATE HOIST TOP DOOR	6" BORE X 59" STROKE 5" BORE X 51" STROKE 3 1/2" BORE X 16" STROKE 3" BORE X 36" STROKE 5 1/2" BORE X 63" STROKE 2 1/2" BORE X 82" STROKE	6" BORE X 59" STROKE 4" BORE X 51" STROKE 5" BORE X 51" STROKE 3 1/2" BORE X 16" STROKE 3" BORE X 36" STROKE 5 1/2" BORE X 63" STROKE 2 1/2" BORE X 82" STROKE
HYDRAULICS	PUMP OIL RESERVOIR VALVES	TYPE: Gear (Front Drive or PTO) CAPACITY: Front Drive - 50 GPM @ 1,200 RPM PTO - 50 GPM @ 1,600 RPM PRESSURE: 1,850 PSI Maximum CAPACITY: 35 Gallons FILTERS: Suction Screen and Return Filter TYPE: 6 Section Spool Controls = Cable, Air or Electric/Air	
CHASSIS REQUIREMENTS	GVWR FRONT AXLE REAR AXLE WHEEL BASE CT/TANDEM	56,000 18,000 38,000 200 - 210 180 - 190	50,000 16,000 34,000 200 - 210 180 - 190

MAXON®

MAXON INDUSTRIES, INC.

1960 Slauson Avenue, Huntington Park, CA 90255

(800) 227-4116 (213) 589-7321

RL0586

MODELS: LOE (EAST) · LOW (WEST)