

SIDE LOADERS WITH A STROKE OF GENIUS

Things have changed in the 25 years since the original Maxon Side Loader was introduced. Changed for the better, to maintain Maxon's lead in high productivity, low-maintenance performance.

Maxon's folding packing ram is just one example. It has always given you the shortest possible cab to hopper distance with its hinged design. The ram folds 90° on the back stroke, cutting the cab to hopper distance to reduce operator fatigue.

Maxon Side Loaders have always had the lowest hopper height, now as low as 42" (36" from the curb). Maxon's high compaction models pack as much as 800 to 1000 lbs. per cubic yard in body sizes of 25, 29, 33 or

37 cubic yards. Utilized body/hopper construction reduces fallback during dumping and you can order your Maxon Side Loader with an open or enclosed hopper.

Over the years, the Side Loader has never been just a side line with Maxon. While others have tried to copy the Maxon design, our engineers have always stayed one step ahead, because we had a head start in building the strongest, easiest to operate, most reliable Side Loaders you can put on your routes.

If you're considering Side Loaders, give us a call for more information.

SIDE LOADERS
MAXON®

MODEL: SL-108



DROP FRAME • STRAIGHT FRAME • CART DUMPER

SIDE LOADERS
PERFORMANCE SPECIFICATIONS

MODEL 108-25 MODEL 108-29 MODEL 108-33 MODEL 108-37

	PITCH-IN HEIGHT PACKING CYCLE CAB TO HOPPER DISTANCE COMPACTION	1" TO 3" ABOVE FRAME 10 SECONDS - CONTINUOUS LOADING 110" - 130" 800 TO 1000 LBS./CUBIC YARD			
BODY & HOPPER	GROSS WEIGHT (Approx.) BODY CAPACITY HOPPER CAPACITY OVERALL LENGTH OVERALL WIDTH	9,750 LBS. 25 CU. YDS. 3/4 CU. YD. 235" 96"	10,000 LBS. 29 CU. YDS. 3/4 CU. YD. 235" 96"	10,500 LBS. 33 CU. YDS. 3/4 CU. YD. 259" 96"	11,000 LBS. 37 CU. YDS. 3/4 CU. YD. 283" 96"
MATERIALS	BODY SIDES BODY ROOF BODY FRONT FLOOR SLOPE BODY REAR FLOOR BODY REAR DOOR HOPPER	12 GAUGE 12 GAUGE 3/16", 50,000 PSI 10 GAUGE 12 GAUGE 5/16", 50,000 PSI			
CYLINDERS	PACKING HOLD-DOWN PANEL HOIST	4" BORE X 30" STROKE 3 1/2" BORE X 16" STROKE 5" BORE X 3-STAGE			
HYDRAULICS	SYSTEM PRESSURE PUMP OIL RESERVOIR	1800 PSI TYPE: Cast Steel CAPACITY: Front Drive or PTO - 30 GPM CAPACITY: 60 Gallons			
CHASSIS REQUIREMENTS	FRONT GAWR REAR GAWR TOTAL GVWR CAB/AXLE APPROX. WB	16,000 23,000 39,000 175 214	16,000 23,000 39,000 175 214	16,000 34,000 50,000 200 238	16,000 34,000 50,000 200 238

MAXON®

MAXON INDUSTRIES, INC.

1960 Slauson Avenue, Huntington Park, CA 90255

(800) 227-4116 (213) 589-7321

RSL586