SHU-PAK CUTS OPERATING COSTS

The original one-man side-loading refuse packer



*Belgium Standard

5HU-PAK

Public works officials and private contractors choose SHU-PAK* because of labor cost efficiencies and lower maintenance costs. SHU-PAK*: Industry leader for over 20 years.

A superior and innovative design, proven dependability for cost-efficient refuse collection

The Belgium Standard SHU-PAK® makes good sense for cities, towns and townships and private contractors looking for cost efficiencies in refuse collection. The SHU-PAK® is ideal for servicing condominiums, partly-rural pick-up routes and areas where maneuverability is a key requirement. Ask us for names of satisfied customers who can give you details of how they have put the SHU-PAK® to work — and saved.



45-degree sloped roof provides added tree clearance and closer curb operation.



One piece rear door is hinged at top and hydraulically operated for fast unloading (optional). Manual or air-actuated safety locks are provided.



A replaceable neoprene seal keeps liquid waste inside until the body is unlocked and dumped.



Ruggedly reinforced drop frame chassis brings the loading height of hopper down to a comfortable loading height 4" above original chassis frame.




Safety-protected manual controls are used for the hoist, crusher panel and optional hydraulic tailgate. Stop, start and emergency palm buttons are provided to control the packer. Electrically-operated micro-switches activate the ram from both sides of the hopper.

Belgium Standard

SHU-PAK

Outstanding features and options to suit every need

Fully enclosed hopper keeps the weather out and the refuse in.





Walk through insulated cab has dual controls with full right-hand controls including hand-operated brake and electrical control panel.



The crusher panel and ram make a powerful combination for compacting refuse and efficient loading.

Choke throat packing design:

- prevents refuse from falling back into hopper
- requires no retention panel
- provides shorter wheel base



Front-mounted crankshaft drive, with large capacity dry-valve pump for quiet on-the-go operation.

FEATURES


SHU-PAK

Steel, low entry walk-through cab with sliding doors Full right-hand stand up driving controls

Right-hand loading step
Automatic transmission
Inside cab location of main
electrical control panel
Fully modified chassis to
accommodate packer
Pack-on-the-move capability
Weatherproof switches
Positive body lock
100% body welds
Floor slope wearplate
Sloped roof on cab
Sloped canopy on hopper

OPTIONS

Unitized body
Hydraulic tailgate
Enclosed hopper
Aluminum body
Left hand step
Back-up alarm



GENERAL SPECIFICATIONS

Model
Capacity
Length of body and packer
Body height above frame
Body overall width
Body and packer weight (lbs.)
Cycle time (sec.)
Single or tandem drive axle

109-25 25 cu./yd. 229'' 90'' 96'' 8,314 10-14

Single

109-29 29 cu./yd. 229'' 102'' 96'' 9,304 10-14 Single

109-33 33 cu./yd. 251" 102" 96" 10,568 10-14 Tandem

109-37

275"

102'

11,023

10-14 Tandem

96"

37 cu./yd.

Some equipment shown or features described may be optional at extra cost.

Because of our commitment to product improvement,

specifications subject to change without notice.



For more information call:

UNITED STATES

Belgium Standard Inc.

Suite 358, 1931 North Meacham Road, Schaumburg, Illinois. 60195 Phone: (312) 397-0003 Telex: 25-3327 CANADA Belgium Standard Industries, 35 University Ave. E., P.O. Box 186,

P.O. Box 186, Waterloo, Ontario. N2J 3Z9 Phone: (519) 885-5220 Telex: 069-55204